



**ALLEN**  
SPORTS

INSTRUCTIONAL OWNER'S MANUAL

**PRODUCT REGISTRATION:**

MAKE SURE TO REGISTER YOUR PURCHASE AT  
<http://allensportsusa.com/about/product-registration>  
TO QUALIFY FOR PRODUCT WARRANTY AND TO RECEIVE  
IMPORTANT PRODUCT NOTIFICATIONS

1

# MODEL YOOGO CZZ CARGO TRAILER

Owner's Manual should be kept for future reference

1. Completely read and understand Owner's Manual before assembling or operating this product.
2. This product should be assembled by an adult.

## IMPORTANT SAFETY INFORMATION

**!WARNING**

- Failure to follow these warnings and assembly instructions could result in serious injury or death!
- Immediately discard all plastic bags and plastic wrapping materials!
- Maximum weight capacity for trailer is 70 pounds.
- Never use this trailer if it becomes damaged!
- Never allow children to assemble, fold, or disassemble this unit!
- Accessories or parcels placed in trailer may cause it to become unstable secure the load.
- Not for use with children or pets.
- Before riding, check that all parts are assembled according to the manufacturer instructions!
- Tires should be inflated to 25-30 PSI ( between 2.5 and 3.0 bar) for maximum control! Check tire pressure before each use!
- Use a foot pump or hand pump to inflate tires! Pressurized air hoses can cause over inflation!
- Periodically re-check all fasteners to make sure they are tight!

**!WARNING**

## SAFE TOWING TIPS

**!WARNING**

- Make sure your bike brakes work properly! Braking distance is increased when pulling a trailer!
- This trailer is wide! Allow extra clearance near curbs, signs, parked cars, and other obstacles!
- A bicycle with trailer attached requires a wide turning radius! Do not turn sharply!
- Do not ride over curbs! Avoid bumps and holes! Always signal your turns!
- Use extra caution when turning on uneven pavement, and going downhill!
- Not for use at high speeds! Do not exceed 10 MPH!
- Do not pull this trailer at night!

**!WARNING**



## FULLY ASSEMBLED TRAILER



## PARTS LIST

### QUANTITY

### DESCRIPTION

1

Frame w/ fabric body,  
and wheel brackets attached

1

Tow bar w/coupler

1

Tow bar foot w/spring pin

2

12" Rear wheels

1

Elastic mesh cargo net



# CONTENT

1. Warnings / Cautions .....	1
2. Parts List .....	2
3. Table of Content .....	3
4. Assembly & Operation .....	4
5. Installing Hitch Arm.....	4
6. Installing Wheels .....	5
7. Installing Mesh Cargo Cover .....	5
8. Attaching Trailer to Bicycle .....	6
9. Folding Storage & Transport.....	7
10. WARRANTY.....	8

**Please Read all instructions and examine contents carefully before assembly.**



## ASSEMBLY AND OPERATION INTRUCTIONS

**STEP 1:** Remove the trailer, wheels, hitch arm and walking kit from the box.



FIGURE 1

**WARNING:** Immediately discard all plastic bags and plastic wrapping materials!

**STEP 2: INSTALL HITCH ARM**

1. Install foot (Fig a) on hitch arm by pressing spring pin and sliding in to hitch arm (Fig b) so pin locks in place in the corresponding hole in the hitch arm.
2. Slide Hitch arm onto frame pin at left front of frame as shown. Fig 1
3. Insert snap pin into the hole in the frame pin to fix arm to frame. Fig 2
4. Close snap pin to lock arm in place. Fig 3.
5. Rotate Arm to align holes in hitch arm and frame bracket and insert the Hand Knob through the hole, and tighten to secure arm to frame. . Fig4-5
6. The handle can be fixed in two positions; Upper position for pull cart. Fig5, and Lower position for bicycle trailer. Fig 6



FIGURE A.



FIGURE B.



FIGURE 1.



FIGURE 2.



FIGURE 3.



## ASSEMBLY AND OPERATION INTRUCTIONS



FIGURE 4.



FIGURE 5.



FIGURE 6.

### STEP 3: INSTALL THE WHEELS

**WARNING:** Immediately discard all plastic bags and plastic wrapping materials!

1. Lift the rear of the trailer so the wheel bracket is off the ground.
2. Position the wheel to insert the axle into the hole. Fig 7-8
3. Slide wheel axle in all the way, and insert the cotter pin through the pin as shown. Fig 7-8



FIGURE 7.



FIGURE 8.

**NOTE:** Wheels must be properly secured. After installation, tug on wheel center to ensure the wheel axle is locked in place.

### STEP 4: USING THE ELASTIC MESH CARGO COVER

1. Open the elastic mesh net, and place over the load so the net can cover the contents completely.
2. Clip the plastic hooks of the net to the D-rings on the cargo trailer fabric body.
3. Make sure the net can contain all your items. If not secured, small items will fall out!



FIGURE 8.1.

**NOTE:** This trailer is for cargo ONLY! It is not designed for the safe transport of children or pets.



## ASSEMBLY AND OPERATION INTRUCTIONS

### STEP 5: ATTACHING TRAILER TO BICYCLE

1. Open snap pin to remove the trailer hitch axle mount . Fig 9
2. Remove rear axle nut or quick release axle and install the trailer hitch axle mount.. Fig 10



FIGURE 9



FIGURE 10

3. Tighten axle nut or quick release skewer securely, testing to see the hitch is unable to move or pull loose. Be careful to position as shown. Fig 11
4. Attach hitch arm to axle mount, and secure the snap pin so the loop of the pin lock is over the pin shaft. Fig 11-15



FIGURE 11.



FIGURE 12.



FIGURE 13.



FIGURE 14.



FIGURE 15.



## ASSEMBLY AND OPERATION INTRUCTIONS

**NOTE:**

**TIPS FOR USE**

1. Distribute load evenly inside trailer. Max. recommended trailer tongue weight at hitch 8-15lbs..
2. Secure cargo to prevent moving or falling out.
3. Maximum load 70 lbs
4. Allow extra room when cornering as the trailer is wide.
5. Pulling a trailer requires extra braking distance. Do not exceed safe speed.
6. Not for transport of flammable or toxic materials.

## FOLDING FOR STORAGE AND TRANSPORT

**NOTE:**

**FOLDING FOR STORAGE AND TRANSPORT**

1. Remove all cargo from inside the trailer compartment.
2. Unclip the trailer hitch snap pin and remove trailer from bicycle frame. The hitch can remain on the bicycle for later use.
3. Unscrew the hand knob connecting locking the hitch arm in position on the frame.
4. Remove the snap pin from the frame pin to allow hitch arm to be removed completely
5. Remove the wheels by first removing the pins inside the frame, then pulling the wheel out.
6. Place wheels and towbar inside trailer for safe keeping.



FIGURE 16

**NOTE:**

**BEFORE EVERY USE**

- Make sure that all parts are in good working order, and that no parts are missing.
- Do not use this product if any parts are broken or missing!
- Check that all fasteners are securely tightened.
- Check the tires to make sure they are properly inflated.
- If you have any questions concerning the proper use of this product after it has been stored, please contact a qualified technician.



**WARNING!: Not for use with children or pets.**



**ALLEN**  
SPORTS

INSTRUCTIONAL  
OWNER'S MANUAL

8

## WARRANTY

## WARRANTY

IF YOUR PRODUCT REQUIRES WARRANTY SERVICE, PLEASE DO NOT RETURN IT TO RETAIL STORE.

PLEASE CONTACT:

ALLEN SPORTS USA  
(800) 722-5536 ~ CUSTOMERSERVICE@ALLENRACKS.COM

Please note that all returns and exchanges are subject to the return policy of the retailer where the product was originally purchased



**ALLEN**  
SPORTS

R. A. ALLEN CO., INC. - 36 Maplewood Rd., Portsmouth, NH 03801, USA

[www.allensportsusa.com](http://www.allensportsusa.com)

Product designed in USA, Made in Ningbo, China